



淬硬鋼 HarednedSteel HRC55-58	淬硬鋼 HarednedSteel HRC>65	沉澱硬化不銹鋼 Precipitation hardeningStainless Steel	普通鋼 Commom Steel HRC<25
●	△	●	●
合金鋼 alloy Steel HRC<45	灰鑄鐵 Grey Cast Iron	銅合金 CopperAlloy	不銹鋼 Stainless steel
△	△	△	△
鈦合金 Titanium Alloy	鋁合金 Aluminum si<9%	鎳基高溫合金 Nicle Based Alloy	複合材料 Composite Material
△	△	△	△

備注：● 非常適合 ○ 比較適合 △ 不適合



R ≤ 6	R < 8		
±0.01	±0.02		
D ≤ 12	D > 12		
0 - 0.020	0 - 0.030		
4 ≤ d ≤ 6	8 ≤ d ≤ 10	12 ≤ d ≤ 16	16 ≤ d ≤ 25
0 - 0.006	0 - 0.009	0 - 0.011	0 - 0.013

商品編號 Product number	半徑(R) Radius of R	刃徑(D) Blade diameter	刃長(Lc) Blade length	柄徑(d) Shank diameter	全長(L) Overall length	刃數 FluteFlute
MH5802BLR200475	2.00	4.0	6.0	4	75	2
MH5802BLR2004100	2.00	4.0	8.0	4	100	2
MH5802BLR300675	3.00	6.0	9.0	6	75	2
MH5802BLR3006100	3.00	6.0	12.0	6	100	2
MH5802BLR400875	4.00	8.0	12.0	8	75	2
MH5802BLR4008100	4.00	8.0	16.0	8	100	2
MH5802BLR50010100	5.00	10.0	20.0	10	100	2
MH5802BLR60012100	6.00	12.0	24.0	12	100	2
MH5802BLR70014100	7.00	14.0	28.0	14	100	2
MH5802BLR80016150	8.00	16.0	32.0	16	150	2
MH5802BLR10020150	10.00	20.0	40.0	20	150	2
MH5802BLR12525150	12.50	25.0	50.0	25	150	2