



淬硬鋼 HarededSteel HRC55-58	淬硬鋼 HarededSteel HRC>65	沉澱硬化不銹鋼 Precipitation hardeningStainless Steel	普通鋼 Commom Steel HRC<25
●	△	●	●
合金鋼 alloy Steel HRC<45	灰鑄鐵 Grey Cast Iron	銅合金 CopperAlloy	不銹鋼 Stainless steel
△	△	△	△
鈦合金 Titanium Alloy	鋁合金 Aluminum si<9%	鎳基高溫合金 Nicle Based Alloy	複合材料 Composite Material
△	△	△	△

備注: ● 非常適合 ○ 比較適合 △ 不適合



D≤12	D>12		
0 -0.020	0 -0.030		
d=6	8≤d≤10	12≤d≤16	d=20
0 -0.008	0 -0.009	0 -0.011	0 -0.013

商品編號 Product number	刃徑(D) Blade diameter	R角 R angle	刃長(Lc) Blade length	柄徑(d) Shank diameter	全長(L) Overall length	刃數 Flute
MH5804RL30R05475	3.0	0.5	6.0	4	75	4
MH5804RL40R05475	4.0	0.5	8.0	4	75	4
MH5804RL40R10475	4.0	1.0	8.0	4	75	4
MH5804RL40R05675	4.0	0.5	8.0	6	75	4
MH5804RL40R10675	4.0	1.0	8.0	6	75	4
MH5804RL40R054100	4.0	0.5	8.0	4	100	4
MH5804RL40R104100	4.0	1.0	8.0	4	100	4
MH5804RL60R05675	6.0	0.5	12.0	6	75	4
MH5804RL60R10675	6.0	1.0	12.0	6	75	4
MH5804RL60R056100	6.0	0.5	12.0	6	100	4
MH5804RL60R106100	6.0	1.0	12.0	6	100	4
MH5804RL80R05875	8.0	0.5	16.0	8	75	4
MH5804RL80R10875	8.0	1.0	16.0	8	75	4
MH5804RL80R058100	8.0	0.5	16.0	8	100	4
MH5804RL80R108100	8.0	1.0	16.0	8	100	4
MH5804RL10R0510100	10.0	0.5	20.0	10	100	4
MH5804RL10R1010100	10.0	1.0	20.0	10	100	4
MH5804RL12R0512100	12.0	0.5	25.0	12	100	4
MH5804RL12R1012100	12.0	1.0	25.0	12	100	4
MH5804RL10R0510150	10.0	1.5	24.0	10	150	4
MH5804RL10R1010150	10.0	2.0	24.0	10	150	4
MH5804RL12R0512150	12.0	1.5	30.0	12	150	4
MH5804RL12R1012150	12.0	2.0	30.0	12	150	4
MH5804RL14R1014100	14.0	1.0	28.0	14	100	4
MH5804RL14R2014100	14.0	2.0	28.0	14	100	4
MH5804RL16R1016150	16.0	1.0	32.0	16	150	4
MH5804RL16R2016150	16.0	2.0	32.0	16	150	4
MH5804RL20R1020150	20.0	1.0	40.0	20	150	4
MH5804RL20R2020150	20.0	2.0	40.0	20	150	4
MH5804RL25R1025150	25.0	1.0	50.0	25	150	4
MH5804RL25R2025150	25.0	2.0	50.0	25	150	4